

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 April 2006 (06.04.2006)

PCT

(10) International Publication Number
WO 2006/036837 A2

(51) International Patent Classification:
A61B 17/08 (2006.01)

(21) International Application Number:
PCT/US2005/034276

(22) International Filing Date:
26 September 2005 (26.09.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/612,857 24 September 2004 (24.09.2004) US
60/663,289 18 March 2005 (18.03.2005) US
60/662,990 18 March 2005 (18.03.2005) US
60/692,781 22 June 2005 (22.06.2005) US

(71) Applicant (for all designated States except US): NMT
MEDICAL, INC. [US/US]; 27 Wormwood Street, Boston,
MA 02210-1625 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CALLAGHAN,
David, J. [US/US]; 43 Buttonwood Street, Unit 2, Boston,
MA 02125 (US). MCLELLAN, Noel [US/US]; 17 Hill-
side Street, Apt. 2, Boston, MA 02120 (US).

(74) Agents: CAVANAUGH, David, L. et al.; Wilmer Cutler
Pickering Hale and Dorr LLP, 60 State Street, Boston, MA
02109 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY,
MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO,
NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK,
SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LI, LV, MC, NL, PL, PT,
RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: OCCLUDER DEVICE DOUBLE SECUREMENT SYSTEM FOR DELIVERY/RECOVERY OF SUCH OCCLUDER
DEVICE



(57) Abstract: Devices, delivery systems and delivery techniques for an occlusion device for the closure of physical anomalies, such as an atrial septal defect, a patent foramen ovale (PFO), and other septal and vascular defects are described. The devices, delivery systems and delivery techniques relate particularly to, but are not limited to, a patent foramen ovale (PFO) occluder made from a polymer tube. Specifically, a petal-shaped occluder with a catch system is provided within a delivery sheath. In certain embodiments, the delivery system includes a first securement system for securing a first end of the occluder and a second securement system for securing a second end of the occluder to a delivery catheter and a delivery wire contained in the delivery system. The securement enable the deployment (and retrieval) of the device. The securement systems enable pushing and pulling of respective ends of the occluder to expand and contract the device by varying its axial length. In one aspect, the first securement system employs a threaded connection and the second securement system employs a suture connection. In another aspect, the first securement system employs a threaded connection and the second securement system employs a collet finger connection. The securement systems are detached when the device has been properly positioned. The securement systems can be manipulated by control systems provided in the control portion of the delivery system.

WO 2006/036837 A2

Occluder Device Double Securement System for Delivery/Recovery of such Occluder Device

RELATED APPLICATIONS

[0001] This application claims the benefit of priority to U.S. Provisional Application No. 60/612,857, filed September 24, 2004, U.S. Provisional Application No. 60/662,990, filed March 18, 2005, U.S. Provisional Application No. 60/663,289, filed March 18, 2005, and U.S. Provisional Application No. 60/692,781, filed June 22, 2005, the disclosures of each of which are incorporated by reference herein.

TECHNICAL FIELD

[0002] This invention relates generally to occlusion devices for the closure of physical anomalies, such as an atrial septal defect, a patent foramen ovale, and other septal and vascular defects. The invention also relates to delivery systems and mechanisms for such devices.

BACKGROUND

[0003] A patent foramen ovale (PFO), illustrated in FIG. 1, is a persistent, one-way, usually flap-like opening in the wall between the right atrium 11 and left atrium 13 of the heart 10. Because left atrial (LA) pressure is normally higher than right atrial (RA) pressure, the flap usually stays closed. Under certain conditions, however, right atrial pressure can exceed left atrial pressure, creating the possibility that blood could pass from the right atrium 11 to the left atrium 13 and blood clots could enter the systemic circulation. It is desirable that this circumstance be eliminated.

[0004] The foramen ovale serves a desired purpose when a fetus is gestating. Because blood is oxygenated through the umbilical cord, and not through the developing lungs, the circulatory system of the fetal heart allows the blood to flow through the foramen ovale as a physiologic conduit for right-to-left shunting. After birth, with the establishment of pulmonary circulation, the increased left atrial blood flow and pressure results in functional closure of the foramen ovale. This functional closure is subsequently followed by anatomical closure of the two over-lapping layers of tissue: septum primum

14 and septum secundum 16. However, a PFO has been shown to persist in a number of adults.

[0005] The presence of a PFO is generally considered to have no therapeutic consequence in otherwise healthy adults. Paradoxical embolism via a PFO is considered in the diagnosis for patients who have suffered a stroke or transient ischemic attack (TIA) in the presence of a PFO and without another identified cause of ischemic stroke. While there is currently no definitive proof of a cause-effect relationship, many studies have confirmed a strong association between the presence of a PFO and the risk for paradoxical embolism or stroke. In addition, there is significant evidence that patients with a PFO who have had a cerebral vascular event are at increased risk for future, recurrent cerebrovascular events.

[0006] Accordingly, patients at such an increased risk are considered for prophylactic medical therapy to reduce the risk of a recurrent embolic event. These patients are commonly treated with oral anticoagulants, which potentially have adverse side effects, such as hemorrhaging, hematoma, and interactions with a variety of other drugs. The use of these drugs can alter a person's recovery and necessitate adjustments in a person's daily living pattern.

[0007] In certain cases, such as when anticoagulation is contraindicated, surgery may be necessary or desirable to close a PFO. The surgery would typically include suturing a PFO closed by attaching septum secundum to septum primum. This sutured attachment can be accomplished using either an interrupted or a continuous stitch and is a common way a surgeon shuts a PFO under direct visualization.

[0008] Umbrella devices and a variety of other similar mechanical closure devices, developed initially for percutaneous closure of atrial septal defects (ASDs), have been used in some instances to close PFOs. These devices potentially allow patients to avoid the side effects often associated with anticoagulation therapies and the risks of invasive surgery. However, umbrella devices and the like that are designed for ASDs are not optimally suited for use as PFO closure devices.

[0009] Currently available septal closure devices present drawbacks, including technically complex implantation procedures. Additionally, there are significant complications due to thrombus, fractures of the components, conduction system

disturbances, perforations of heart tissue, and residual leaks. Many devices have high septal profile and include large masses of foreign material, which may lead to unfavorable body adaptation of a device. Given that ASD devices are designed to occlude holes, many lack anatomic conformability to the flap-like anatomy of PFOs. Thus, when inserting an ASD device to close a PFO, the narrow opening and the thin flap may form impediments to proper deployment. Even if an occlusive seal is formed, the device may be deployed in the heart on an angle, leaving some components insecurely seated against the septum and, thereby, risking thrombus formation due to hemodynamic disturbances. Finally, some septal closure devices are complex to manufacture, which may result in inconsistent product performance.

[0010] Various delivery systems have been used to deliver occluders and other medical devices through body lumens. Some delivery systems of the prior art are used to deliver devices that readily expand to a delivered configuration when removed from the delivery system. Such delivery systems are not generally suited for delivering a device that does not readily expand into the delivered configuration. Further, the delivery systems of the prior art may not allow verification of the position of the device prior to full deployment of the device. Finally delivery systems of the prior art may not be suitable to manipulate the configuration of the device in a secure manner to allow for complete deployment of the device.

[0011] The devices and techniques disclosed herein are designed to address these and other deficiencies of prior art septal closure devices and techniques for delivering and retrieving such devices.

SUMMARY OF THE INVENTION

[0012] These and other aspects and embodiments of the disclosure are illustrated and described below.

[0013] This description discloses several delivery devices and techniques for delivering an implant into a desired location within the body. This delivery technique relates particularly to, but is not limited to, a septal occluder made from a polymer tube. These delivery techniques, in addition to use with septal occluders, could be applied to

other medical devices, such as other expandable devices constructed from an underlying tubular structure.

[0014] In one aspect, a delivery system is disclosed for delivering an occluder that closes an aperture in septal tissue. The occluder includes a first side adapted to be disposed on one side of the septal tissue and a second side adapted to be disposed on the opposite side of the septal tissue. The first and second sides are adapted to occlude the aperture upon deployment of the device at its intended delivery location. The device also includes a catch system that maintains the configuration of the device once it has been deployed.

[0015] According to at least some embodiments, the device is formed from a tube. According to some embodiments, the tube includes a material selected from the group consisting of metals, shape memory materials, alloys, polymers, bioabsorbable polymers, and combinations thereof. In particular embodiments, the tube includes a shape memory polymer. In particular embodiments, the tube includes nitinol. In some embodiments, the tube is formed by rolling a flat piece of material into a tubular form. According to some embodiments, the device is formed by cutting the tube. The device is placed in its deployment configuration by reducing the axial length of the device.

[0016] According to some embodiments, the catch system reduces and maintains the axial length of the device. Also, varied constructions could be used to maintain the axial dimension of the device. In one form, catch elements such as, for example, balls, attached to a delivery wire could be used to maintain the axial dimension of the device. In a different construction, a locking mechanism could be used. Preferably, if a locking mechanism is used, it secures both sides of the device in the locked position with a single locking element. In some embodiments, a catch element secures the ends of the occluder in a compressed position. Preferably, if a catch mechanism is used, it secures both sides of the device in the deployed position with a single element.

[0017] In another aspect, the present invention provides a device for occluding an aperture in septal tissue, including a first side adapted to be disposed on one side of the septal tissue and a second side adapted to be disposed on the opposite side of the septal

tissue. The first and second sides are adapted to occlude the defect when the device is deployed at its intended delivery location. Each of the first and second sides includes loops. The device further includes a catch system that maintains the configuration of the device once it has been deployed. The loops of the first and second sides and the catch system cooperate to provide a compressive force to the septal tissue surrounding the aperture.

[0018] According to some embodiments, each of the first and second sides includes at least two loops. In particular embodiments, each of the first and second sides includes four or six loops. Of course, the most desirable number of loops on each side will depend on a variety of anatomical and manufacturing factors. According to some embodiments, the device also includes a central tube that connects the first and second sides.

[0019] The delivery system may be used to deliver an occluder in which at least one of the first and second sides further includes a tissue scaffold. The tissue scaffold includes a material selected from the group consisting of polyester fabrics, Teflon-based materials, polyurethanes, metals, polyvinyl alcohol (PVA), extracellular matrix (ECM) or other bioengineered materials, synthetic bioabsorbable polymeric scaffolds, collagen, and combinations thereof. In particular embodiments, the tissue scaffold includes nitinol.

[0020] The delivery system includes a first and a second securement system. The first securement system may be any one of a number of configurations. First, a delivery wire may be used to secure the distal end of the occluder onto the delivery system. When a delivery wire is used, the distal end of the delivery wire may be threaded and cooperate with a corresponding threaded portion on the occluder. In a preferred form, the threaded portion may have male threads on the occluder and female threads on the delivery wire. Alternatively, a ball and clasp, other interlocking system may be used.

[0021] The second securement system may be any one of a number of configurations. In one aspect it may be a threaded connection between the delivery system and the occluder. In another aspect, the second securement system is a collet system that includes fingers, which are configured to fit within a groove in the occluder and thus secure the occluder to the delivery system when the fingers are disposed in the

groove. A collet sheath is moveable with respect to the fingers and when the collet fingers are disposed within the collet sheath, the fingers are configured to fit within the groove provided on the occluder.

[0022] In one aspect, a delivery system for the device is provided within (and includes) a delivery sheath. In certain embodiments, the delivery system includes a first securement system for securing a first end of the occluder and a second securement system for securing a second end of the occluder. The securement systems connect the occluder to first and second catheters contained in the delivery system and enable deployment and/or retrieval of the occluder. The catheters are preferably able to move relative to each other. The securement systems enable pushing and pulling of respective ends of the occluder by manipulating the catheters to expand and contract the device. The first securement system may employ a threaded connection and the second securement system may employ a suture connection. The securement systems are detached when the device has been properly positioned.

[0023] In a further aspect of the invention, the first securement system secures a distal end of a catching system of the device and the second securement system secures a proximal end of the device. A first catheter connects to the first securement system and a second catheter connects to the second securement system. In certain embodiments, the second catheter encloses the first catheter in its central lumen. In one aspect, the device is deployed by inserting the delivery system, removing the sheath, expanding the petals of a distal portion of the device, and expanding the petals of a proximal portion of the device. The delivery system can be detached by detaching the first and second securement systems, e.g., by unscrewing the first securement system and by cutting and removing the sutures. In another aspect, the deployed device is retrieved by contracting the petals of a proximal portion of the device using the second catheter, advancing the sheath over a proximal portion of the device, contracting the petals of a distal portion of the device using the first catheter and advancing the sheath over the distal portion of the device. The occluder can then be repositioned or removed.

[0024] In another aspect, a delivery system is disclosed for delivering an occluder that closes an aperture in septal tissue. The occluder includes a first side adapted to be disposed on one side of the septal tissue and a second side adapted to be disposed on the

opposite side of the septal tissue. The first and second sides are adapted to occlude the aperture upon deployment of the device at its intended delivery location. The device also employs a catch system that maintains the configuration of the device once it has been deployed. The occluder may be held in its deployment configuration by the catch element.

[0025] In one aspect, a delivery system for the device is provided within a delivery sheath. In certain embodiments, the delivery system includes a first securement system for securing a first end of the occluder and a second securement system for securing a second end of the occluder. The securement systems connect the occluder to first and second extrusions, e.g., a catheter or a wire, contained in the delivery system and enable deployment and/or recovery of the occluder. The extrusions are preferably able to move relative to each other. The securement systems enable pushing and pulling of respective ends of the occluder by manipulating the extrusions to expand and contract the device by varying its axial length. The first securement system may employ a threaded connection. The second securement system may also employ a threaded connection. The securement systems are detached when the device has been properly positioned. The securement systems can be manipulated by control systems provided in the control portion of the delivery system.

[0026] In one preferred embodiment, the invention provides a axially collapsible occluder, a means for collapsing and expanding the occluder by changing the distance between the distal and proximal ends of the occluder, and a means for keeping the axial distance between the proximal and distal ends of the occluder fixed after its deployment.

[0027] These and other aspects and embodiments of the disclosure are illustrated and described below.

BRIEF DESCRIPTION OF THE DRAWINGS

In the Drawings:

- [0028] FIG. 1 is a schematic representation of a human heart including various septal defects;
- [0029] FIGS. 2A-2D are isometric views of an embodiment of an occluder for use with disclosed delivery systems and techniques;
- [0030] FIG. 2E illustrates a deployed occluder according to an aspect of the disclosure;
- [0031] FIG. 3A illustrates insertion of an occluder in a human subject using a delivery system in accordance with an aspect of the disclosure;
- [0032] FIG. 3B illustrates introduction of the occluder in a human heart using a delivery system in accordance with an aspect of the disclosure;
- [0033] FIGS. 4A-4D are side views of a delivery assembly for delivering an occluder to a septal defect according to an aspect of the disclosure;
- [0034] FIG. 5 is a side elevational view of a delivery system attached to an occluder in deployed configuration according to an aspect of the disclosure;
- [0035] FIG. 6 is an exploded cross-sectional side view of a delivery system attached to an occluder in deployed configuration according to an aspect of the disclosure;
- [0036] FIG. 7 is an exploded cross-sectional side view of the control portion of a delivery system according to an aspect of the disclosure;
- [0037] FIG. 8 is an enlarged cross-sectional side view of the catheter portion of a delivery system attached to an occluder according to an aspect of the disclosure;
- [0038] FIG. 9 is a cross-sectional side view of the catheter portion of the delivery system attached to a collapsed occluder according to an aspect of the disclosure;
- [0039] FIG. 10 is a cross-sectional side view of one step in a deployment sequence according to an aspect of the disclosure;
- [0040] FIG. 11 is a cross-sectional side view of one step in a deployment sequence according to an aspect of the disclosure;

- [0041] FIG. 12 is a cross-sectional side view of one step in a deployment sequence according to an aspect of the disclosure;
- [0042] FIG. 13 is a cross-sectional side view of one step in a detachment sequence according to an aspect of the disclosure;
- [0043] FIG. 14 is a cross-sectional side view of one step in a detachment sequence according to an aspect of the disclosure;
- [0044] FIG. 15 is a cross-sectional side view of one step in a detachment sequence according to an aspect of the disclosure;
- [0045] FIG. 16 is a cross-sectional side view of one step in a retrieval sequence according to an aspect of the disclosure;
- [0046] FIG. 17 is a cross-sectional side view of one step in a retrieval sequence according to an aspect of the disclosure;
- [0047] FIG. 18 is a cross-sectional side view of one step in a retrieval sequence according to an aspect of the disclosure; and
- [0048] FIG. 19 is a cross-sectional side view of one step in a retrieval sequence according to an aspect of the disclosure.
- [0049] FIG. 20 illustrates a cross-sectional schematic of a deployed occluder according to an aspect of the disclosure;
- [0050] FIG. 21 illustrates a cross-sectional side view of several components of the delivery system according to one embodiment of disclosure;
- [0051] FIG. 22 is an axial cross-sectional drawing of an occluder, in a delivery configuration, according to an embodiment of the disclosure;
- [0052] FIG. 23 is a detail view of the delivery wire according to an aspect of one embodiment of the disclosure;
- [0053] FIG. 24 is a configuration for a first securement system according to an embodiment of the disclosure;
- [0054] FIGS. 25A, 25B, 26A, 26B, 27A and 27B are alternative configurations for the first securement system according to aspects of the disclosure;

[0055] FIGS. 28 and 29 are detail cross-sectional side view of the delivery system during two steps in the deployment process according to one aspect of the disclosure;

[0056] FIG. 30 is a detail view of the collet finger according to one aspect of the disclosure;

[0057] FIG. 31 is a detail cross-sectional side view of the collet system in the splayed configuration;

[0058] FIG. 32A is a detail cross-sectional view of the collet system in the constrained configuration;

[0059] FIG. 32B is a cross-section taken along lines 32B-32B in FIG. 32A;

[0060] FIG. 33 is a detail sectional view of another embodiment of the collet system according to the disclosure;

[0061] FIGS. 34-37 are sectional views of an alternative delivery system according to an aspect of the disclosure;

[0062] FIG. 38A is a front cross-sectional view of a delivery catheter according to one embodiment of the disclosure;

[0063] FIG. 38B is a side cross-sectional view of a delivery catheter with sutures according to one embodiment of the disclosure;

[0064] FIG. 38C is an elevational view of a delivery catheter with sutures secured to an occluder according to one embodiment of the disclosure;

[0065] FIG. 38D is an elevational end view of delivery catheter along lines 38D of FIG. 38C; and

[0066] FIG. 39 is a sectional view of a delivery assembly during a step in the deployment process according to one aspect of the disclosure.

DETAILED DESCRIPTION

[0067] The present disclosure provides devices, delivery/retrieval systems and techniques for delivering such devices intended to occlude an aperture within body tissue. In particular and as described in detail below, the described occluder may be used for closing an ASD or PFO in the atrial septum of a heart. Although the embodiments are described with reference to an ASD or PFO, one skilled in the art will recognize that the device and methods of the present invention may be used to treat other anatomical conditions. As such, the invention should not be considered limited in applicability to any particular anatomical condition. In addition, the systems and methods for delivery and retrieval, and for catching a device in a deployed state, which are aspects of the present invention may also be used in connection with other types of devices besides an occluder, in particular, devices having tubular profiles.

[0068] FIG. 1 illustrates a human heart 10, having a right atrium 11 and a left atrium 13 and including various anatomical apertures 18a and 18b. The atrial septum 12 includes septum primum 14 and septum secundum 16. The anatomy of the septum 12 varies widely within the population. In some people, septum primum 14 extends to and overlaps with septum secundum 16. The septum primum 14 may be quite thin. When the anatomical apertures 18a is present, blood could travel through the anatomical aperture 18a between septum primum 14 and septum secundum 16 (referred to as "the PFO tunnel"). Additionally or alternatively, the presence of an ASD could permit blood to travel through an aperture in the septal tissue, such as through the anatomical aperture 18b.

[0069] In this application, "distal" refers to the direction away from a catheter insertion location and "proximal" refers to the direction nearer the insertion location. Additionally, the term "delivery configuration" refers to the configuration of a device, such as an occluder, when it has a reduced profile in a delivery catheter. The term "deployed configuration" refers to the configuration of the device, such as an occluder, when it has deployed from the catheter, such as at the desired implantation location.

[0070] FIGS. 2A-D illustrates an exemplary occluder with which systems and techniques disclosed herein may be used. An occluder 70, for example, can be formed by cutting a series of slits on tube 25. As shown in FIGS. 2A-2D, distal petals 32 are produced by cutting slits 31 in the upper portion of tube 25 according to the cutting

pattern shown in FIG. 2A. As shown in FIG. 2B, the distal portion of the tube 25 is cut in half to form half sections 91a and 91b. The half sections 91a and 91b are further cut to a proximal distance from distal tip 39 into quarter sections 92a, 93a, 92b, and 93b. The cuts are discontinued and quarter sections 92a and 92b form half section 94a at distal tip 39, and quarter sections 93a and 93b form half section 94b at distal tip 39. Upon application of force F_d to distal tip 39, struts defined by slits 31 bow and twist outward to form distal petals 32 in distal side 30, as shown in FIGS. 2C-2D. The movement of the struts during deployment is such that the struts rotate in an orthogonal plane relative to the axis of the device. Central tube 22 may be constrained during the application of force F_d , or any combination of forces sufficient to reduce the axial length of the tube 25 may be applied. One end of each of distal petals 32 originates from central tube 22, while the other end originates from distal tip 39 (FIGS. 2B-2C). Proximal petals 42 may be formed in proximal side 40, as shown in FIGS. 2B-2D, making slits 41 between central tube 22 and proximal end 44, using the same cutting pattern described above.

[0071] The tube(s) 25 forming occluder 70 may be formed from a biocompatible metal or polymer. In at least some embodiments, the occluder 70 is formed of a bioabsorbable polymer, or a shape memory polymer. Shape memory polymers can be advantageous so that the structure of the device assists in pressing the PFO tunnel closed. In other embodiments, the occluder 70 is formed of a biocompatible metal, such as a shape memory alloy (e.g., nitinol). The thermal shape memory and/or superelastic properties of shape memory polymers and alloys permit the occluder 70 to resume and maintain its intended shape in vivo despite being distorted during the delivery process. Alternatively, or additionally, the occluder 70 may be formed of a bioabsorbable metal, such as iron, magnesium, or combinations of these and similar materials. Exemplary bioabsorbable polymers include polyhydroxyalkanoate compositions, for example poly-4-hydroxybutyrate (P4HB) compositions, disclosed in U.S. Patent No. 6,610,764, entitled *Polyhydroxyalkanoate Compositions Having Controlled Degradation Rate* and U.S. Patent No. 6,548,569, entitled *Medical Devices and Applications of Polyhydroxyalkanoate Polymers*, both of which are incorporated by reference in their entirety.

[0072] The cross-sectional shape of tube 25 may be circular or polygonal, for example square, or hexagonal. The slits 31 and 41 may be disposed on the face of the polygon (i.e., the flat part) or on the intersection of the faces.

[0073] The tube can be injection molded, extruded, or constructed of a sheet of material and rolled into a tube. The sheet of material could be a single ply sheet or multiple ply. The slits that form the struts could be cut or stamped into the sheet prior to rolling the sheet into a tube to connect the ends to form an enclosed cross section. Various geometrical cross sections are possible including circular, square, hexagonal and octagonal and the joint could be at the vertex or along the flat of a wall if the cross section is of a particular geometry. Various attachment techniques could be used to join the ends of the sheet to form a tube, including welding, heat adhesives, non-heat adhesives and other joining techniques suitable for in-vivo application.

[0074] The petal configuration is the deployed configuration. The occluder 70 can be secured in the petal configuration by a catch system that holds the ends of the tube 25 together, certain embodiments of which are described below. Use of the terms distal and proximal sides or portions 30 and 40, respectively, include the petals that are formed on the distal and proximal sides.

[0075] The embodiment described in conjunction with FIGS. 2A-2D has similarities to the device disclosed in U.S. Patent Application No. 10/890,784, entitled *Tubular Patent Foramen Ovale (PFO) Closure Device with Locking Mechanism*, filed on July 14, 2004; U.S. Patent Application No. 60/549,741, entitled *Delivery/Recovery System for Clover Leaf Septal Occluder*, filed on March 3, 2004; U.S. Patent Application No. 60/612,857, entitled *Delivery/Recovery Systems for PFO Occluder with Catch System*, filed September 24, 2004; U.S. Patent Application No. 60/663,289, filed March 18, 2005, entitled *Delivery/Recovery System for PFO Occluder with Catch System*; U.S. Patent Application No. 60/662,990, filed March 18, 2004, entitled *Suture Delivery/Recovery System for PFO Occluder with Catch System*; all of which have the same assignee as the present application, and are incorporated by reference in their entirety. These incorporated documents describe how a device can be formed by making cuts or slits in a tube and compressing the ends, and how to deliver such a device.

[0076] The transformable design of occluder 70 enables occluder 70 to be delivered in a low profile, tubular form and to be converted readily, i.e., by reducing the axial

length, in place to the high-profile deployed configuration. Moreover, the conversion can readily be effected by forcing distal end 39 and proximal end 44 together. For example, distal side 30 and proximal side 40 of occluder 70 may be deployed in separate steps, or both distal side 30 and proximal side 40 of occluder 70 may be exposed (e.g., out of the delivery catheter) prior to engaging the catch system and deployed together as the catch element is engaged. Use of the terms distal and proximal side 30 and 40, respectively, include the loops or other geometries and configurations that are formed on the distal and proximal sides, respectively.

[0077] Occluder 70 may be prepared for delivery to an aperture 18 in any one of several ways. Slits 31 and 41 may be cut such that tube 25 bends into its intended configuration following deployment in vivo. Specifically, slits 31 and 41 may be cut to produce struts 32 and 42 of a thickness that facilitates the bending and formation of loops 32 and 42 upon the application of forces F_d and/or F_p during deployment. See FIGS. 2B and 2C. Alternatively and/or additionally, a tube 25 formed of a shape memory material may be preformed into its intended configuration ex vivo so that it will recover its preformed shape once deployed in vivo. According to at least some embodiments, this preforming technique produces more reliable deployment and bending of occluder 70 in vivo. An intermediate approach may also be used: tube 25 may be only slightly preformed ex vivo such that it is predisposed to bend into its intended shape in vivo upon application of forces F_d and F_p .

[0078] FIG. 2E shows a deployed occluder 70 in a human heart with a catch element 50 engaged. The term "catch system" describes the portion/aspect of the device that secures the device in the deployed configuration, it may be a single piece or a group of connected or assembled pieces. The catch element is the portion of the catch system that engages with the occluder to hold the occluder in the deployed configuration and is described in more detail below. The configuration illustrated is a simplified schematic view of the occluder 70 illustrated in FIGS. 2A-2D. This particular type of occluder 70 and catch element 50 are described for purposes of illustration and explanation; of course, other types of occluders (with different types of catch elements or systems) can be deployed using the deployment systems described herein. The catch element 50, as illustrated, is disposed in an axially central location in the occluder 70 and is schematically illustrated as a separate piece than the occluder 70. In a preferred

embodiment, the catch element may be fixed to one end of the tube 25 that forms occluder 70. For example, a flange 52 may be fixed to the distal tip 39 of the tube 25 that forms the distal and proximal petals 32 and 42.

[0079] In general, references to "occluder 70" herein may be inclusive of catch element 50, depending on the context, for example, unless separately listed or otherwise stated. One end of tube 25 is able to move with respect to the catch element 50 (and especially the catch system) so that the distal and proximal petals 32 and 42 can move from the delivery configuration to the deployed configuration. The inside surface of the tube 25 is able to slide over the catch element 50 so that, when the proximal end 44 of the occluder 70 rests against the surface of the proximal flange 56, the occluder 70 is secured in its deployed configuration. The catch element 50 is included in the catch system that includes a portion for connection to the delivery/recovery system, including, for example, a threaded section illustrated in FIG. 2E. The threaded section is an adaptation designed to fit with the desired type of securement system according to a preferred embodiment discussed herein and is not necessarily an inherent feature of the catch element 50. Occluder 70 also includes an additional feature, such as threads or a groove 72 (as illustrated) to provide another connection between the occluder and the delivery/recovery system.

[0080] FIG. 3A illustrates the insertion of an occluder in a human subject 122 using a delivery assembly 124 in accordance with an aspect of the disclosure. A portion of delivery assembly 124, including an occluder and a delivery mechanism for the occluder, which can be externally manipulated by a clinician, is inserted into the subject through an incision point 126. The distal end of the delivery assembly is advanced toward and into the heart 10 until the distal end is in proximity to the defect to be closed, as seen in FIG. 3B.

[0081] Figure 4A illustrates the occluder 70 in the distal end of the delivery assembly 124, which includes a delivery system 140. A delivery system generally includes a delivery catheter, a delivery wire and a delivery sheath. Because the occluder 70 is delivered percutaneously, the device is secured to the delivery system 140 so that the occluder 70 can be placed accurately at the desired delivery location. Securement systems are provided that attach the occluder to the delivery components. The securement systems are configured to provide accurate delivery of the occluder to the

desired delivery location and allow for a controlled deployment so that the position of the device as it is being deployed can be monitored. Also, a device deployed according to this system is able to be retrieved and repositioned until the final stage of the deployment process. In some circumstances, after the final stage of the deployment process, the device can be retrieved. The manner in which the occluder is secured to the delivery system 140 and the process for deployment and/or retrieval of the occluder 70 are described in detail below.

[0082] As illustrated in FIG. 4A, the delivery system 140 includes a delivery sheath 144 and a delivery catheter 148. A delivery string or wire 150 extends the length of the delivery assembly to the distal end of the occluder 70. The delivery system 140 constrains the occluder 70 in its elongated delivery configuration. As shown in FIG. 4B, a delivery sheath 144 containing the occluder 70 is first inserted into the right atrium 11 of the patient's heart.

[0083] The delivery system, including the delivery sheath 144, may next be inserted through aperture 18 located in the septal tissue 12 (which, in this example, is a PFO tunnel) and into the left atrium 13. Distal side 30 of occluder 70 is then exposed into the left atrium 13 by withdrawing the delivery sheath 144 then pulling force F_1 is applied to delivery string or wire 150 such that, for example, a catch element 50 passes through the central tube 22, thereby securing distal side 30 into its deployed state. Delivery sheath 144 is withdrawn further through the aperture 18 and into the right atrium 11, such that central tube 22 is positioned through the aperture 18. As shown in FIG. 4C, proximal side 40 of occluder 70 is then exposed into the right atrium 11, and a relative force between the proximal end 44 of the occluder 70 and the delivery string or wire 150 is applied such that a catch element 50 passes through the proximal end 44 of the occluder 70, thereby securing the proximal side 40 of the occluder into its deployed state. Of course, the occluder 70 should remain in position during deployment of each side of the occluder 70 and pulling forces on the septum tissue should be avoided.

[0084] As shown in FIG. 4D, when properly deployed, occluder 70 is disposed through the aperture 18 with a portion of the device on the proximal side and another portion of the device on the distal side. The distal side 30 and proximal side 40 exert a compressive force against septum primum 14 and septum secundum 16 in the left 13 and right 11 atria, respectively, to close the aperture 18, e.g. the PFO. When the occluder 70

is properly located, the securement systems are detached releasing the occluder from the delivery system. This delivery system is then removed from the heart. In the event occluder 70 is not properly deployed after performing the delivery sequence, the occluder 70 may be recovered by reversing the steps of the delivery sequence.

[0085] As mentioned above, during the deployment of the occluder 70 in the delivery system 140 described in connection with FIGS. 4A-4D, the occluder 70 is secured to the delivery system 140 at two locations on the occluder 70 so that the occluder 70 can be formed (i.e., compressed) into its deployed configuration. In a preferred form, there are two securements to the delivery assembly 140. A first securement is toward the distal end of the occluder 70 whereby the occluder 70 is held by the delivery string or wire 150. The second securement is at the proximal end 44 of the occluder 70 whereby the occluder 70 is held by the delivery catheter 148. The first and second securements allow the proximal and distal ends of the occluder 70 to be forced together so that the occluder 70 can move from the delivery configuration to the deployed configuration. They also allow the occluder 70 to be forced back into its low profile delivery configuration for redeployment or retrieval. Even if the occluder 70 were constructed from shape memory material (e.g., Nitinol), the occluder 70 would preferably be secured to the delivery assembly 140 by first and second securements.

[0086] Both securement systems are able to move relative to one another during the delivery process and as a result, both securement systems cause the occluder 70 to move into the deployed configuration. In the process of delivering the occluder 70, the second securement system is typically released and the first securement system is held while the position of the occluder 70 is evaluated by, for example, fluoroscopy, and if the position of the occluder 70 is appropriate, the first securement system is released.

[0087] FIG. 5 shows delivery assembly 200, which includes a delivery system 220 with an occluder 224 to be delivered. The attached occluder 224 is shown in a deployed configuration for convenience only. Prior to deployment, the occluder 224 would normally be in a low-profile configuration, contained within a delivery sheath 242. FIG. 6 shows delivery assembly 200 in an exploded cross-sectional side view. For convenience, the illustrations have been divided into two parts comprising a control portion 230 of the delivery system 220, and a catheter portion 250 of the delivery system 220 with the attached occluder 224, with the connection indicated by broken line L1. The

control portion 230 extends from a delivery wire control rod 232 to a delivery sheath control 240. The catheter portion 250 extends from the delivery sheath control 240 to the end of the delivery system 220 where the occluder 224 is attached. The control portion 230 remains external to the patient and incorporates the features provided for operation of the catheter portion 250 of the delivery system 220. FIG. 7 shows an enlarged cross-sectional side view of the control portion 230. FIG. 8 shows an enlarged cross-sectional side view of the catheter portion 250 and the occluder 224. The basic components of the delivery system 220 are described below by reference to FIGS. 5-8 collectively.

[0088] For convenience in describing the function of the controls, the catheter portion 250 is discussed first. Now, referring to FIG. 6, in the catheter portion 250, a delivery sheath 242 encloses the components that are used to deliver occluder 224. A delivery catheter 244 contains an inner delivery wire 246. Both of the delivery catheter 244 and delivery wire 246 connect to the occluder 224 during delivery. Although it may be considered advantageous to eliminate the central lumen in certain embodiments, in other embodiments the delivery wire 246 could also be tubular. The delivery wire 246 should have sufficient tensile and compressive stiffness to withstand the steps required for the deployment and retrieval sequence. In this embodiment, the delivery wire 246 has a stiffer proximal portion and a more flexible distal portion. The delivery catheter 244 also has a stiffer proximal portion and a more flexible distal portion. The combination of stiffness and flexibility facilitates delivery and positioning of the occluder 224. Both the delivery catheter 244 and the delivery wire 246 may be made of two lengths of two different materials joined together in order to provide the requisite degree of stiffness in each portion of the element. Alternatively, the variation of stiffness can be the result of annealing, or some other material treatment process. The more flexible distal portion prevents undue distortion of the septal tissue during the delivery sequence. The delivery wire is further described infra.

[0089] Still referring to FIG. 6, the control portion of the delivery system 230 includes respective controls for the delivery sheath 242, the delivery catheter 244 and the delivery wire 246. The delivery wire 246 can be advanced and retracted linearly, in the direction indicated by arrow D', and rotated with respect to the linear axis of the delivery system 220, in the direction indicated by arrow C'. The delivery wire control rod 232 is a rod-like element that provides both linear and rotational control for the delivery wire 246.

The delivery wire control rod 232 slides linearly in the direction indicated by arrow C and rotates, with respect to the linear axis of the delivery system 220, in the direction indicated by arrow D to provide the corresponding motion in the delivery wire 246. The delivery catheter 244 can be advanced and retracted linearly, in the direction indicated by arrow A', and rotated, with respect to the linear axis of the delivery system 220, in the direction indicated by arrow B'. A delivery catheter control 234 is a tubular element that provides linear control for the delivery catheter 244, by sliding linearly in the direction indicated by arrow A. A delivery catheter rotational control 238 provides rotational control of the delivery catheter 244, by rotating, with respect to the linear axis of the delivery system 220, in the direction indicated by arrow B. The delivery wire control rod 232 connects to the delivery wire 246 inside the delivery catheter control 234. A perfusion port 236 is provided to permit introduction of fluids into the delivery sheath 242. The delivery sheath 242 can also be rotated, with respect to the linear axis of the delivery system 220, in the direction indicated by arrow F' and extended and retracted linearly along the direction indicated by arrow E'. A delivery sheath control 240 provides linear and rotational control of the delivery sheath 242. The delivery sheath control 240 can be rotated, with respect to the linear axis of the delivery system 220, in the direction indicated by arrow F and slid linearly in the direction indicated by arrow E to induce the corresponding motion in the delivery sheath 242. Thus, all three of the delivery sheath 242, delivery catheter 244 and delivery wire 246 can be independently extended and retracted along and rotated around the longitudinal axis of the delivery system 220 relative to each other using the appropriate controls. The controls are preferably designed to ergonomic specifications. Coordinated operation of the delivery sheath 242, delivery catheter 244 and delivery wire 246 allows for delivery (or retrieval) of the occluder 224. Although in the illustrated embodiment, each element of the catheter portion 250 can be manipulated individually and directly by the user of the delivery system 220, in alternate embodiments, the required operations could be partially or completely automated or synchronized.

[0090] Since the occluder 224 is delivered percutaneously, the delivery system 220 must be able to be secured so that the occluder 224 can be placed accurately at the desired delivery location and transformed into its deployed configuration. Securement systems are provided that attach the delivery components to the occluder 224. The securement

systems are typically released serially after proper placement of the occluder 224 is confirmed. The securement systems are configured to provide accurate delivery of the occluder 224 to the desired delivery location and allow for a controlled deployment. Also, a device deployed according to this mechanism is able to be retrieved and repositioned until the final stage of the deployment process. It is also possible to retrieve the device once it has been fully released.

[0091] Referring to FIG. 8, the delivery catheter 244 and delivery wire 246 both contain features of securement systems on their distal ends for connecting to the occluder 224 and a catch system 180. The delivery wire 246 terminates in a threaded portion 258 having a funnel-like profile. The threaded portion 258 screws onto a mated threaded portion 182 provided on the proximal flange 184 of the catch element 188 for the occluder 224. These two threaded portions cooperatively form the first securement system. The delivery catheter 244 terminates in a threaded portion 256 having a funnel-like profile. The threaded portion 256 screws onto a mated threaded portion 226 provided on the frame of occluder 224. These two threaded portions cooperatively form the second securement system. The first securement system in effect secures the distal end of the occluder to the delivery system 220. The second securement system secures the proximal end 44 of the occluder 224 to the delivery system 220. The two-securement systems cooperatively allow the ends of the occluder 224 to be forced together or apart for deployment or retrieval. The funnel-like profile is useful for locating the corresponding threaded portion of the occluder 224 or the catch element 188 for attachment. The funnel provides a channeling or guiding function. The funnel also helps the delivery system 220 attach to the occluder 224 at extreme angles. The specific geometry of the funnel tips can be modified to achieve better alignment with the device. Application of torque in the appropriate direction engages or disengages each securement system by screwing together or unscrewing the respective elements from each other. The terms "distal" and "proximal" generally refer to the disposition of the securement locations while the occluder 224 is in the delivery configuration in a delivery sheath, but the orientation of the securement systems may change during or after the delivery process.

[0092] Still referring to FIG. 8, in a presently preferred embodiment, the threaded portions 256 and 258 are both female threaded, while the corresponding threaded portion 182 of the proximal flange 184 and threaded portion 226 are male threaded. This

configuration has several advantages. First, a male thread in the occluder eliminates a cavity in the occluder 224 in which blood can stagnate and promote clotting. Second, the profile of the occluder 224 is reduced by using the male thread. Finally, the female connectors on the delivery system 220 can be provided with the funnel-like guides described above. In alternate embodiments, the male threads may be disposed on threaded portions 256 and 258. Also, threaded portions 256 and 258 need not have the same type of threads.

[0093] Deployment of the occluder to a desired site is typically a multi-step operation. In FIGS. 5 and 6, the occluder 224 is shown outside the delivery catheter for purposes of illustration. As shown in FIG. 9, the delivery sheath 242 contains occluder 224 in its elongated, delivery form, with the catch element 188 disengaged. As discussed above with reference to FIGS. 3A and 3B, the distal end of the delivery sheath 242 with the enclosed occluder 224 is first inserted into the right atrium 11 of the patient's heart. The distal end of the delivery sheath 242 with the enclosed occluder 224 may next be inserted through the anatomical aperture 18a located in the septal tissue 12, and into the left atrium 13. The distal side 30 of occluder 224 is then deployed into the left atrium 13. The deployment process is described further below. As shown in FIG. 10, the delivery sheath 242 is withdrawn through the anatomical aperture 18a into the right atrium 11, such that central tube 22 of the occluder 224 is positioned through the anatomical aperture 18a. As shown in FIG. 11, the proximal side 40 of the occluder 224 is then deployed into the right atrium 11. When properly deployed, the central tube 22 is disposed at the anatomical aperture 18a, and the distal side 30 and proximal side 40 exert a compressive force against septum primum 14 in the left atrium 13 and septum secundum 16 in the right atrium 11, respectively, to close the anatomical aperture 18a, e.g. the PFO. When the occluder 224 is properly deployed, the delivery system 220 is detached from the occluder 224, and the delivery sheath 242 with the delivery catheter 244 and delivery wire 246 are then withdrawn from the heart. In the event that the occluder 224 is not properly deployed after performing the procedure described above, the occluder 224 may be recovered by reversing the steps of the delivery sequence. These sequences are described in more detail below.

[0094] FIG. 9 illustrates the initial step for a typical delivery sequence in accordance with one aspect of the disclosure, a high level view of which is shown in FIG.

3B. The occluder 224 and catch system 180 are secured to the delivery wire 246 and to the delivery catheter 244, respectively. The female threaded portion 256 of the delivery catheter 244 is screwed onto the male threaded portion 226 of the occluder 224. The female threaded portion 258 of the delivery wire 246 is screwed onto the male threaded portion 182 of the catch element 188 of the occluder 224. The distal end of the delivery sheath 242 with the enclosed occluder 224 is inserted through the aperture to be occluded, such as the anatomical aperture 18a of FIG. 1, to approximately the midpoint of the occluder 224.

[0095] Referring now to FIG. 10, the distal side 30 of the occluder 224 is deployed on the distal side of the aperture in the left atrium 13. The distal portion 30 is deployed by first retracting the delivery sheath 242 to expose the distal portion 30 of the occluder 224. The axial length of the occluder 224 is then reduced by applying pulling force F_1 on delivery wire 246 with sufficient force to cause the catch element 188 to be pulled through the central tube 22 of the occluder 224 and the distal portion 30 of the occluder 224 to compress and distal petals 32 to form. Force F_2 is simultaneously applied to the delivery catheter 244 to hold the occluder 224 stationary. The central tube 22 of the occluder 224 catches on the catch element 188. This holds the distal petals 32 in place while the remainder of the deployment sequence is carried out.

[0096] Referring now to FIG. 11, the proximal side 40 of the occluder 224 is deployed on the proximal side of the aperture in the right atrium 11. The proximal portion 40 is deployed by first retracting the delivery sheath 242 to expose the proximal portion 40 of the occluder 224. The proximal petals 42 are then deployed by simultaneously advancing the delivery catheter 244 by applying force F_4 and retracting the delivery wire 246 by applying force F_5 to maintain the position of the occluder 224. Eventually, the proximal end 44 of the occluder 224 is pushed over the proximal end 44 of the catch element 188 and the occluder 224 is caught on the proximal flange 184 of the catch element 188. The final configuration is illustrated in FIG. 12. The occluder 224 can now be evaluated for proper deployment at the desired location.

[0097] The occluder 224 can be evaluated for proper deployment with the delivery system 220 attached or at least partially detached. The delivery system 220 can be partially detached by releasing one of the securement systems provided by the delivery catheter 244 and the delivery wire 246. As shown in FIG. 13, according to one preferred

embodiment, to evaluate the proper deployment of the occluder, if desired, the delivery sheath 242 can be further retracted and the delivery catheter 244 can be detached from the occluder 224. The delivery catheter 244 can be detached by applying torque to unscrew the delivery catheter 244 from the proximal threaded portion 226 of the occluder 224 and retracting the delivery catheter 244. The delivery wire 246 continues to secure the occluder 224, as illustrated in FIG. 14. This affords the clinician a substantially unobstructed view of the occluder delivery site in order to evaluate the placement of the occluder 224. In addition, the more flexible distal portions of the delivery catheter 244 and the delivery wire 246 allow the distal end of the delivery system 220 and the deployed occluder to be re-positioned so that the view is not obstructed. The positioning of the occluder 224 can be evaluated using fluoroscopy or other appropriate techniques. If the delivery or deployment is not satisfactory, then the delivery system 220 can be used to retrieve the occluder 224. If delivery catheter 244 has been detached, it is reattached by advancing the threaded portion 256 of the delivery catheter 244 toward the threaded portion 226 of the occluder 224 and applying torque until the delivery catheter 244 is threaded onto the occluder 224. As mentioned before, the funnel-like shape of the threaded portion 256 of the delivery catheter 244 helps to guide the reattachment of this securement system. A similar technique is used to reattach the delivery wire 246 if needed.

[0098] Once the occluder 224 is successfully deployed, the delivery system 220 can be detached in the sequence shown in FIGS. 13-15. As illustrated in FIG. 13, the delivery sheath 242 is partially retracted by applying force F_{12} . Also, the delivery catheter 244 is detached by applying torque F_{14} to unscrew the threaded portion 256 of the delivery catheter 244 from the threaded portion 226 of the occluder 224. Force F_{13} is then applied to retract the delivery catheter 244 while simultaneously advancing the delivery wire 246 by applying force F_{15} to maintain the position of the occluder 224. The occluder 224 remains attached to the delivery system 220 by the second securement system provided by the delivery wire 246. As discussed above, if retrieval is desired for any reason, the occluder 224 can readily be returned to its low-profile configuration and removed at this point. As shown in FIG. 14, the delivery catheter 244 can be further retracted by applying force F_{16} to provide an unobstructed view of occluder 224, again while the delivery wire 246 remains attached. As illustrated in FIG. 15, if the deployment is

successful, then the delivery wire 246 can be detached by applying torque F_{17} to unscrew the threaded portion 258 of the delivery wire 246 from the threaded portion 182 of the catch element 188. The torque applied to remove the delivery wire 246 and the delivery catheter 244 can be either clockwise or counterclockwise depending on the design of the device. The delivery wire 246 can be retracted by applying force F_{18} . The occluder 224 is now fully deployed.

[0099] Referring now to FIG. 16, if retrieval is desired, the process involves reattaching the delivery catheter 244 and delivery wire 246 as mentioned above. Then force F_6 is applied to the delivery catheter 244 to pull the proximal portion 40 of the occluder 224 over the proximal end of the catch element 188. As the axial length of the occluder 224 is increased, the proximal petals 42 are unformed and the proximal portion 40 of the occluder 224 returns to its tubular profile. Referring to FIG. 17, force F_8 is applied to the delivery sheath 242 to advance the delivery sheath 242 over the proximal portion 40 of the occluder 224 and retain the proximal portion 40 of the occluder 224 in the low-profile configuration. Also, force F_7 is applied to delivery wire 246 in order to release the distal portion 30 of the occluder 224 and further increase the axial length of the occluder 224. Referring now to FIG. 18, the distal portion 30 of the occluder 224 is fully extended back into its low-profile configuration and forces F_9 and F_{10} are applied to the delivery sheath 242 and the delivery catheter 244 in order to retrieve the occluder 224 back into delivery sheath 242. Referring to FIG. 19, the delivery sheath 242 and enclosed occluder 224 are removed from the anatomical aperture 18a and can further be fully removed from the heart 10 by applying force F_{11} . This step can also be used as a starting point for redeployment of the occluder 224, i.e., the sequence shown beginning in FIG. 9.

[00100] The components of an alternate preferred embodiment of the invention are described in connection with FIGS. 20-24. FIG. 20 illustrates an occluder 310 with a distal side 30 and a proximal side 40 that are connected by central tube 22. The configuration illustrated is a simplified schematic view of the occluder illustrated in FIGS. 2A-2D. Of course, other types of occluders can be deployed using this delivery system. The occluder includes a catch system 320 that includes a distal flange 322, a catch body 324 and a catch element 326 in the shape of a cone. The catch system 320 is disposed in an axially central location in the occluder 310. Although schematically illustrated as a separate piece than the proximal side and distal side loops 40 and 30,

respectively, of the occluder, the catch system 320 may be a single piece, or even fixed to one end of the tube that forms the proximal and distal loops by an adhesive, ultrasonic welding, or the like. For example, the flange 322 may be fixed to the end of the tube that forms the loops. The device can be formed from a single component or multiple components that are fixed together. The catch body 324 is disposed axially within the inside surface of the tube that forms the loops. The tube is able to move with respect to the catch system (and the catch body) so that the petals can move from the delivery configuration to the deployed configuration. The inside surface of the tube 335 is able to slide over the catch element 326 so that, when the proximal tip of the occluder 310 rests against the flat surface 326a of the catch element 326, the occluder 310 is secured in its deployed configuration.

[00101] As shown in FIG. 20, the first securement system 330 includes a threaded component 332, illustrated as a male thread, and corresponding threads on a corresponding female portion described below in connection with FIGS. 22 and 23. The second securement system 340 includes a groove 314 on the proximal portion 40 of the occluder 310 that cooperates with a collet system 344 described below in connection with FIGS. 21 and 22. As shown in FIG. 21, the collet system 344 also includes collet fingers 346 that are configured to have ends that fit within the groove 314 on the occluder 310. The collet system also includes a collet tube 348 onto which the collet fingers 346 are mounted and a collet sheath 350 that is movable with respect to the collet tube 348. In one embodiment, the collet fingers 346 are constructed of nitinol and have a splayed configuration when at rest as illustrated in FIG. 21. More detail regarding the construction of the construction of the collet fingers 346 is provided below. As the end of the collet sheath 350 is moved over the collet fingers 346, the collet fingers 346 are moved radially inward and when occluder 310 is being positioned in the delivery system, the collet fingers 346 are moved radially inward and engage the groove 314 on the occluder 310 (illustrated on the left side of FIG. 22). The collet sheath 350, collet tube 348 and collet fingers 346 are described in more detail below.

[00102] FIG. 22 illustrates a delivery system of a preferred embodiment of the invention. Specifically, the occluder 310 is disposed within the delivery sheath 356. Within the delivery sheath 356 are the components that are used to secure the occluder 310 during delivery and are (typically) released serially after proper placement of the

occluder 310 is confirmed. The first securement system 330 and the second securement system 340 are each illustrated as securing the occluder 310 for delivery to the desired delivery location within the body. The securement systems 330 and 340 are configured to provide accurate delivery of the occluder 310 to the desired delivery location and allow for a controlled deployment so that the position of the device as it is being deployed can be monitored. Also, an occluder 310 deployed according to this system is able to be retrieved and repositioned until the final stage of the deployment process. Even after the final stage of the deployment process, the occluder 310 can be retrieved.

[00103] FIG. 22 also illustrates the second securement system 340 in an engaged configuration. Specifically, the collet fingers 346 are disposed in the collet sheath 350 so that the collet fingers 346 engage groove 314 on the occluder 310. When the collet sheath 350 is disposed in this configuration, the occluder 310 is secured by the collet fingers 346 against axial motion with respect to the collet sheath 350 and collet tube 348. Similarly, when the delivery wire 380 is secured in an engaged configuration, the occluder 310 is secured against axial motion with respect to the delivery wire 380. Thus, the occluder 310 is secured during delivery and the controlled motion of the collet sheath 350/collet tube 348 and the delivery wire 380 can deploy the occluder 310.

[00104] As illustrated in FIG. 22, the delivery wire 380 is threaded into the first securement system 330 by a threaded connection. As illustrated in FIG. 22, the female threads can be disposed on the delivery wire 380 and the male threads can be disposed on the occluder 310. FIG. 24 illustrates an alternative embodiment of a first securement system, designated 390, in which the male threaded portion 392 is disposed on the delivery wire 380 and the female threaded portion 394 is disposed on the occluder 310.

[00105] In a presently preferred embodiment, the male threads are disposed on the occluder 310 and the female threads are disposed on the delivery wire 380. This configuration has several advantages. First, the occluder 310 does not need a female connector and there is no cavity in which blood can stagnate and promote clotting. Second, the space required for the threaded connector 392 on the occluder 310 is diminished. Finally, a female connector on the delivery wire 380 may allow for a more smooth deployment of the occluder 310.

[00106] The first securement system interconnects the delivery wire 380 to the threaded portion on the occluder 310. Representative embodiments of the first

securement system and its components are illustrated in more detail in FIGS. 23 and 24. In FIG. 23, the threaded portion 386, interconnects the delivery wire 380 and the threaded portion 332 on the occluder 310, illustrated in FIG. 20.

[00107] Referring again to FIG. 23, the delivery wire 380 has a more rigid section 382 and a more flexible section 384. In general, the flexible section 384 is distal to the more rigid section and is provided on the delivery end of the delivery wire 380. The delivery wire 380 can be any kind of flexible elongate member such as a wire, tube, hypotube, coil, or other hollow or solid constructions. The delivery wire 380 can be made from any material suitable for medical applications. Exemplary materials include metals and alloys suitable for medical applications, including stainless steel (such as "304 Stainless") and MP35N, polymers (such as nitinol), or any other suitable materials. The variation of stiffness can be the result of annealing; other material treatment process, or it may be a result of different materials being joined together. The amount of flexibility, or rigidity, can vary depending on the type of occluder being delivered and the delivery location within the body. The length of the flexible section 384 would typically be about the length of the occluder 310 in its delivery configuration. That is, the occluder 310 in the delivery configuration would surround the flexible portion of the delivery wire 380. The length of the flexible section 384, however, can be varied. The distal end of the delivery wire 380 includes a threaded attachment portion 386 on the end of the flexible section 384, described in detail below. The threaded portion 386 is illustrated as a female thread.

[00108] FIGS. 25A, 25B, 26A, 26B, 27A, and 27B illustrate alternative embodiments of the first securement system 330. Generically, all of the securement embodiments described can be properly described as interlocking systems. Each of these embodiments of the first securement system can be used with the threaded or collet connection for the second securement system and provide alternatives which may be appropriate for different kinds of occluding devices or other devices that could be delivered by the delivery system described in this application

[00109] FIGS. 25A and 25B illustrate a ball and claw type attachment. In place of a screw type attachment, a ball 410 is disposed on the occluder and two or more claws 412 are sized to secure the ball 410 within the claws 412. The claws 412 are disposed at the distal end of the delivery wire 380. Two claws 412 are illustrated in FIG. 25B. The

claws 412 operate under a similar principle as the collet design described previously. Specifically, there is a claw sheath 414 that is axially movable with respect to the claws 412. As illustrated in FIG. 25B the claws 412 splay out in the at rest configuration. When the claws 412 are in the claw sheath 414, the claws 412 are sized to secure the ball 410. Thus the configuration allows for a secure placement of the occluder on the delivery system. When the occluder is ready to be released claw sheath 414 is withdrawn and the claws 412 splay out to the at rest configuration. Thus the occluder is released from the first securement system.

[00110] FIGS. 26A and 26B illustrate a pin-through-hole connector 420. In this embodiment, fingers 422 includes pins 424 that are disposed in an aperture in the occluder. As the example illustrates, the transverse aperture 428 is formed in the occluder and the transverse aperture 428 is sized to receive the pins 424. When the fingers 422 including pins 424 are in a sheath 426, the pins 424 are secured within the transverse aperture 428. Thus the configuration allows for a secure placement of the occluder on the delivery system. When the occluder is ready to be released a sheath 426 is withdrawn and the pins 424 spring back to the unbiased position similar to the fingers in the collet system. Thus the occluder is released from the first securement system.

[00111] In another embodiment of the first securement system, illustrated in FIGS. 27A and 27B, a pair of cooperating configurations are secured when disposed within a sheath and separable when the sheath is withdrawn. This is a type of interlocking system 440. In this example, the lock is achieved using a combination of two C-shaped elements. Specifically, as illustrated, the occluder has a portion 442 that extends in an axial direction and is adapted to mate with a delivery wire 444. The portion 442 and the delivery wire 444 have cooperating extensions 446, 448 respectively that are able to interlock as illustrated in FIG. 27A. The system as illustrated has an interlocking elbow/arm attachment 450, 452 on each of the protrusion and the delivery wire. A variety of interlocking configurations are possible and the concept should not be limited to the configuration illustrated. When the interlocking system is disposed within a sheath 454, the cooperating extension cannot move with respect to each other. Thus the configuration allows for a secure placement of the occluder on the delivery system. When the cooperating extensions are extended beyond the sheath 454, the interlocking system can release and the occluder is released from the first securement system.

[00112] Any of the previous embodiments described in FIGS. 20-27B can be deployed in a manner illustrated in FIGS. 28 and 29. FIG. 28 illustrates the occluder 310 in its deployed configuration. To deploy the occluder 310, the delivery sheath 356 is withdrawn to expose the distal side loops 30 and then the proximal side loops 40 into the defect to be occluded. During this time the catch element 326 is engaged so that the occluder 310 is secured in the deployed configuration. Once the occluder 310 is in the deployed configuration the collet sheath 350 is withdrawn and the collet fingers 346 are unconstrained by the collet sheath 350 and are allowed to move radially outward to the unbiased condition, as illustrated in FIG. 29. Once the collet fingers 346 move radially outward the tips of the collet fingers 346 move away from the groove 314 in the occluder 310. Accordingly, the occluder 310 is only attached to the delivery by the first securement system 330. In this position, the clinician is able to evaluate the position of the occluder 310 to make sure that the device is properly positioned.

[00113] The process of retrieving an occluder varies based on the state of the delivery when the decision to retrieve the occluder is made. If the second and first securement systems are still attached and the catch system has not secured the device in the deployed configuration, then the retrieval process is simply a reversal of the deployment process. The second securement system is pulled and the device can be withdrawn into delivery sheath 356 and removed from the body.

[00114] If the catch system has secured the device in a deployed configuration, and the second and first securement systems are still attached, the process is the same with the addition of moving the catch element of the occluder relative to the second securement so that the device can be elongated. Once that occurs, the device can be withdrawn as described above.

[00115] The retrieval process for an occluder in which the second securement system is a collet system, which has been disengaged, requires an additional step. The collet system is advanced until the collet fingers are in alignment with the groove on the occluder. Next the collet sheath is advanced over the collet fingers such that the fingertips fit within the groove on the occluder. By pulling on the collet tube with the occluder firmly secured, the device can be returned to its collapsed state and retrieved into the delivery assembly. From this point the delivery process can be restarted.

[00116] FIG. 30 illustrates a detail view of a collet finger 346 and the collet sheath 350. The collet finger 346 is configured to be about 20 degrees from the base of the collet finger 346, the dimension identified as θ in FIG. 30. The collet finger 346 can extend from the collet tube 348 approximately 0.25 in., the dimension identified as "a" in FIG. 30. The distance "a" can be from 0.1 in. to 0.5 in. The angle θ can vary from low single digits to approximately 70 degrees. In general, as the length of "a" is decreased, the angle desired for θ would increase. The collet finger 346 includes a radially inwardly extending protrusion 347, which is formed by a bend in the nitinol finger. The bend is preferably 90 degrees and the dimensions of the protrusion are selected to securely fit within the groove 314. As illustrated in FIG. 20, supra, the groove 314, for example, could be 0.02 – 0.04 in. in axial length and 0.005-0.020 in radial depth. The groove 314 is illustrated as a circumferential groove; alternatively, recesses can be formed in part of the occluder 310 to receive the collet fingers 346. It is preferable that the collet fingers 346 have a close fit but not an interference fit in the axial direction. This assures that the collet system can move the device without significant slippage. It is also preferable that the protrusion does not come into contact with the bottom of the groove 314 (the innermost radial surface). This assists the deployment of the occluder.

[00117] FIGS. 31, 32A, and 32B illustrate alternative embodiments of the second securement system. The fingers are formed by cutting sections from a nitinol hypotube that has, for example, a .0075 in. wall thickness. The inner diameter could be, for example, 0.098 in. and the outer diameter could be 0.117 in. The thickness of the hypotube could be as large as 0.050 in. or more. Nitinol is a desirable material due to its superelastic characteristics. Other superelastic materials or simply springy material may be used. Of course, the materials would have to be suitable for use in a medical device. The nitinol hypotube is cut so that the fingers extend from one side and the hypotube ring is uncut at the other end. As an example, FIG. 31 illustrates a cross section where the hypotube is disposed on an end of the collet tube 348. The nitinol ring 355 is disposed on the outside surface of the collet tube. The nitinol ring 355 may be affixed to the collet tube 348 by a variety of known techniques such as a suitable adhesive.

[00118] FIGS. 32A and 32B illustrate the side and end view of representative collet fingers 346. In a preferred embodiment, there are four collet fingers 346 that are used to secure the occluder in the delivery system. In alternate embodiments, there may be as

few as two collet fingers 346 or as many as 8. One practical limitation is the circumferential size of the collet fingers 346 and the rigidity of the collet fingers 346 as they are used to deploy the occluder. In the embodiment illustrated in FIG. 32B, the four collet fingers 346 are formed by cutting away a 1/8th section of the cross section and forming four equally spaced collet fingers 346. During the formation process the roundness of the collet finger 346 along the circumference can be modified to adjust the bendability of the collet fingers 346.

[00119] FIG. 33 illustrates another embodiment of the collet fingers 346. In this embodiment, the collet fingers 346 include a bend 358 between the base ring 355 and the protrusion 347. As illustrated the bend 358 is in the approximate halfway between the base ring 355 and the protrusion 347. The bend 358 can be almost any configuration but the bend 358, as illustrated, allows for force to be applied to the occluder and have the configuration of the collet fingers 346 be such that it does not extend so far away from the collet tube 348 in the radial direction. This allows the occluder to have a more controlled delivery because of the increased forces applied and a more compact system because the collet fingers 346 do not extend radially away from the collet tube 348 as far.

[00120] Another embodiment of the second and first securement system of the delivery system, illustrated in FIGS. 34-37, uses a filament instead of a delivery wire. As shown in FIG. 34, the second securement system 340 is illustrated as the collet system 344, which is largely the same as in the previous embodiment. Of course, other securement systems included a threaded connection can be used. The first securement system includes an eyelet 510 around which a flexible filament 512 can be fastened or looped. The flexible filament can be a suture thread (monofilament or polyfilament), a thin metallic wire or other flexible material that can withstand a tension load.

[00121] The deployment of the occluder is effected by withdrawing the delivery sheath 356 to expose and let the distal petals 30 on the distal side of the occluder expand as illustrated in FIG. 35. Once the distal petals 30 are deployed by the catch element 326, the delivery sheath 356 is repositioned to the deployment site of the proximal petals 40 and the proximal petals 40 are exposed as illustrated in FIG. 36. The filament is pulled to cause the catch element at the proximal side of the occluder to be secured. Once the catch element secures the occluder in the deployed configuration, the collet system is released in the manner described above and illustrated in FIG. 37. Once the collet system is

released, the position may be evaluated. If the position is satisfactory, filament 510 is pulled through the eyelet and removed from the body. Either a delivery wire, a tube or filament is appropriate for the second securement system depending on the design considerations. For example, if the occluder in the delivery configuration lacks sufficient column strength to have the delivery sheath pull back without affecting the position of the device in the delivery system, a delivery wire that has some column strength would be more desirable.

[00122] An alternative recovery sequence is also provided. The recovery process for a device in which the second securement (e.g., collet) system has been disengaged, the process requires an additional step. For systems in which a retrieval capability is desired, additional filaments can be attached to the proximal tip of the occluder. For example, with reference to FIG. 34, filaments 514 are attached to the proximal end 44 of the occluder 570 through holes 516. The filaments 514 can be attached in a variety of locations, for example, they can be looped around one of the proximal loops on the proximal side of the device. When the filaments 514 are provided, the clinician would orient the delivery catheter 548 (as illustrated in FIG. 38B) to the proximal end 44 of the occluder 570 and then pull on the filaments 514 to uncatch the system so that the profile of the device can be reduced and reinserted into the delivery catheter. In an embodiment where the filament 514 is present and the device is deployed satisfactorily, the filaments 514 can be cut or otherwise withdrawn from the body.

[00123] FIG. 38A illustrates an end view of the construction of the delivery catheter 548. The delivery catheter 548 has a central lumen 556 and secondary lumens 554 surrounding the central lumen 556. The outer lumens 554 are used to provide a passageway for containing sutures 558 secured to the occluder 570, illustrated in FIG. 38C, as the attachment mechanism for the second securement system 340 and passed through the delivery catheter 548 to the user for manipulating the second securement system. Although four outer lumens 554 are shown, any number of lumens may be provided suitable for use in the delivery system 340. A sufficient number of sutures 558 should be provided in order to securely attach the occluder 570 and permit the necessary operations. The sutures 558 are shown in FIG. 38B, which illustrates sheath delivery 544 which contains delivery catheter 548. Referring again to FIG. 38C, the delivery catheter 548 is connected to the proximal end 44 of the occluder 570 via the sutures 558 which

attach to holes 560 provided in the occluder 570. The sutures 558 are threaded through the holes 560 and can be readily detached by, e.g., cutting the sutures and pulling through the delivery catheter 548. Attachment of the sutures 558 to the occluder 570 may be provided in a number of ways, such as providing hooks or a flange on the occluder 570, around which the sutures can be wrapped or fastened, or wrapping the sutures 558 around the proximal petals 42. The sutures 558 can also be embedded into the proximal end 44 of the occluder 570. The flexible filament used to provide the thread can be a suture thread (monofilament or polyfilament), a thin metallic wire or other flexible material that can withstand a tension load.

[00124] FIG. 39 illustrates a complete delivery assembly 700 with the occluder 570 in place for delivery and deployment at the deployment site. As shown, the occluder 570 is in its elongated, low profile configuration. The occluder 570 is secured at its distal end 39 by the first securement system 330 to the delivery wire 380 and at its proximal end 44 by the second securement system 550 to the delivery catheter 548. The occluder 570, delivery wire 380 and delivery catheter 548 are contained within the sheath 544. The occluder 570 can be detached from the first securement system 330 by unscrewing the delivery wire 330, which is connected by threaded portion 386 to threaded portion 332. The occluder 570 can be detached from the second securement system 550 by removing the sutures 558, for example, by pulling on them from the user end of the delivery system.

[00125] The embodiments and techniques described here are described preferably for use with a device made of a polymer and formed from a single tube, such that the tube is a single monolithic material. The catch mechanism can be all or partly monolithic or integral with the tubular structure, or there can be an absence of any type of bonding or rigid connection to the rest of the tubular structure, in which case there may be some spring force or other force that holds the locking mechanism in place. While the device is thus shown as being substantially formed from a single tubular body, the catch mechanism as described in the embodiments above could be used with other types of devices, including those formed from many pieces, and including devices formed from other materials, including metals, polymers, stainless steel or nitinol.

[00126] The term "bioabsorbable," as used in the description above, is also understood to mean "bioresorbable."

[00127] While the description above refers to strings, filaments, sutures and wires, and while the term "wire" might convey a more rigid piece than a string, a suture or a filament, all these terms are essentially interchangeable, and further include embodiments in which the wire, string, suture or filament is a hollow tube or conduit to allow another wire, as needed, to pass through its longitudinal axis. Each wire, string, suture and filament can be composed of one or more wires, strings, sutures and filaments.

[00128] In cases in which the device is made of a polymer, it can be desirable to add an additive or coating to the material to make it radiopaque to make it more visible in a wider variety of imaging techniques.

[00129] It will be appreciated that while a particular sequence of steps has been shown and described for purposes of explanation, the sequence may be varied in certain respects, or the steps may be combined, while still obtaining the desired deployment or in some cases to effect deployment in a particular way. For example, the delivery sheath may be advanced or retracted at varying times and in varying degrees, the proximal and distal portions of the occluder may be deployed in to the petal configuration in a different sequence, etc. In addition, the steps could be automated.

CLAIMS

1. A collapsible medical device for occluding an aperture in a body and a delivery system, the medical device having a first configuration as a reduced profile and a second configuration as an expanded profile, the medical device being adapted to be delivered through the delivery system into a desired delivery location, the medical device comprising:
 - a proximal side and a distal side,
 - a first attachment for securing the distal side of the device to the delivery system,
 - and
 - a second attachment for securing the proximal side of the device to the delivery system,wherein the relative movement of the second attachment and the first attachment changes the configuration of the device from the reduced profile configuration to the expanded profile configuration and release of at least one of the second attachment and the first attachment does not involve a twisting motion of the delivery system.
2. The medical device recited in claim 1, wherein the second attachment further includes a recess in the device that is adapted to cooperate with projection on the delivery system that fits the recess.
3. The medical device recited in claim 2, wherein the first attachment is a threaded connection disposed at a central axis of the device and is released from the delivery device by twisting.
4. The medical device recited in claim 2, wherein the first attachment is a threaded connection disposed on a surface of the device and is released from the delivery device by twisting.

5. The medical device recited in claim 2, wherein the recess in the device is an annular groove.
6. The medical device recited in claim 5, wherein the device includes an outer surface and an annular groove located on the outer surface.
7. The medical device recited in claim 2, wherein the device includes an outer surface and the recess is located on the outer surface.
8. The medical device recited in claim 6, wherein the annular groove is adapted to receive a plurality of radially inwardly facing projections.
9. The medical device recited in claim 1, wherein the device includes an aperture adapted to contain a recovery string attached to the device so that the device, once deployed can be retrieved by the recovery string.
10. The medical device recited in claim 1, wherein the first attachment includes a threaded connection and the device includes male threads.
11. The medical device recited in claim 1, wherein the first attachment is a string looped at an axially central location on the device.
12. The medical device recited in claim 1, wherein the first attachment at the one of the proximal or distal sides of the device includes a generally rounded element that is configured to cooperate with the delivery system such that when the generally rounded element is secured by the delivery system, the distal side of the medical device is secured to the delivery system and movable with respect to the second attachment.
13. The medical device recited in claim 1, wherein the first attachment includes an element with an aperture configured to accept pins in a radial direction such that when pins in the delivery system are disposed in the aperture, the medical device is secured to the delivery system and moveable with respect to the second attachment.

14. The medical device recited in claim 1, wherein the first attachment includes a C-shaped element that is configured to cooperate with the delivery system, such that when the C-shaped element is attached to a corresponding C-shaped element from the delivery system, the medical device is secured to the delivery system and the distal side is movable with respect to the second attachment.

15. A collapsible medical device for occluding an aperture in a body, the medical device having a first configuration as a reduced profile and a second configuration as an expanded profile, the medical device being adapted to be delivered through a delivery system into a desired delivery location, the medical device comprising:

- a proximal side and a distal side,

- a first attachment for securing the device to the delivery system, and

- a second attachment for securing the device to the delivery system including a string,

wherein the relative movement of the first attachment and the second attachment changes the configuration of the device from the reduced profile configuration to the expanded profile and at least one of the first attachment and second attachment is threaded.

16. The medical device recited in claim 15, wherein both second and first attachments are threaded.

17. A collapsible medical device for occluding an aperture in a body, the medical device having a first configuration as a reduced profile and a second configuration as an expanded profile, the medical device being adapted to be delivered through the delivery system into a desired delivery location, the medical device comprising:

- a proximal side and a distal side,

a first attachment at the distal side of the device for securing the device to the delivery system, and

a second attachment for securing the device to the delivery system including a recess on an outer surface of the device adapted to receive a part of the delivery system to secure the device in the delivery system,

wherein the relative movement of the first attachment and the second attachment changes the configuration of the device from the reduced profile configuration to the expanded profile.

18. An apparatus to occlude an aperture within a body, the apparatus including a medical device having a first configuration as a reduced profile and a second configuration as an expanded profile and a delivery system adapted to deliver the medical device to a desired delivery location,

the medical device comprises:

a proximal side and a distal side,

a second attachment for securing the device to the delivery system,

a first attachment for securing the device to the delivery system, and

the delivery system comprises:

proximal and distal attachment locations adapted to secure the device to the delivery system, the proximal attachment location cooperating with one of the first and second attachments, and the distal attachment location cooperating with the other of the one of the first and second attachments,

wherein the relative movement of the second attachment and the first attachment changes the configuration of the device from the reduced profile to the expanded profile and releasing at least one of the first and second attachments from the delivery device does not involve a twisting motion of the delivery device.

19. The apparatus recited in claim 18, wherein the second attachment further includes a recess in the device and a cooperating projection on the delivery system that fits the recess.
20. The apparatus recited in claim 19, further comprising a delivery system that includes a tube from which a projection extends and a sheath that moves axially with respect to the tube.
21. The apparatus recited in claim 20, wherein the tube includes axially projecting fingers.
22. The apparatus recited in claim 21, wherein the tube includes 4 fingers.
23. The apparatus recited in claim 19, wherein the recess is an axial groove.
24. The apparatus recited in claim 21, wherein the fingers are biased in the radially outward direction.
25. The apparatus recited in claim 24, wherein the fingers include a first bend to extend the device in the radially outward direction and a second bend such that the distal end of the finger is in the axial direction.
26. The apparatus of claim 18, wherein the device includes a recovery string attached to the device.
27. The apparatus recited in claim 18, wherein the first attachment is a threaded fastener.
28. The apparatus recited in claim 18, wherein the first attachment is a string looped at an axially central location on the device.
29. The apparatus recited in claim 18, wherein the first attachment includes a generally rounded element that is configured to cooperate with a delivery system, such that when the generally rounded element is secured by the delivery system, the distal end

of the medical device is secured to the delivery system and movable with respect to the second attachment.

30. The apparatus recited in claim 18, wherein the first attachment includes an element with an aperture configured to accept one or more pins in a radial direction such that when the one or more pins in the delivery system are disposed in the aperture the medical device is secured to the delivery system and moveable with respect to the second attachment.

31. The apparatus recited in claim 18, wherein the first attachment includes a C-shaped element that is configured to cooperate with the delivery system such that when the C-shaped element is attached to a corresponding C-shaped element from the delivery system, the medical device is secured to the delivery system and the distal side is movable with respect to the second attachment.

32. A medical apparatus for occluding an aperture in a body, the apparatus including a medical device having a first configuration as a reduced profile and a second configuration as an expanded profile, the medical device being adapted to be delivered through the delivery system into a desired delivery location, the apparatus comprising:

a proximal side and a distal side,

a first means for attaching the device to the delivery system, and

a second means for attaching the device to the delivery system,

wherein the relative movement of the first means and the second means changes the configuration of the device from the reduced profile to the expanded profile, wherein at least one of the means for attaching is released without twisting.

33. The medical apparatus as recited in claim 32, wherein the one of the first and second means for attaching includes a sheath and the one of the first and second means is released by moving the sheath axially.

34. The medical apparatus recited in claim 33, wherein apparatus includes a wire and the wire includes a threaded connection to the device and at least one of the first and second means for attaching is releasable by unscrewing the threaded connection.

35. The medical apparatus recited in claim 32, wherein at least one of the first and second means for attaching the device to the delivery system includes a threaded connection.

36. The medical apparatus recited in claim 35, wherein the threaded connection includes male threads on the device.

37. The medical apparatus recited in claim 32, wherein one of the first and second means for attaching the device to the delivery system includes a threaded connection.

38. The medical apparatus recited in claim 37, wherein the threaded connector includes male threads on the device.

39. A method for delivering a medical device to a desired delivery location, the device being attached to a delivery system by a first attachment at a proximal side of the device and a second attachment at a distal side of the device, the method including:

locating the delivery system at the desired delivery location,

deploying the distal side of the device by causing relative movement between the first and second attachments,

deploying the proximal side of the device by causing relative motion between the first and second attachments,

releasing one of the proximal and distal attachments by withdrawing a sheath, and

releasing the other of the proximal and distal attachments by twisting a threaded connector.

40. The method of claim 39, wherein the delivery system includes fingers to attach the device to the delivery system, and the fingers are released when the sheath is withdrawn.

41. A medical device comprising:

a proximal side and a distal side,

a first means for attaching the device to a delivery system at a distal location of the delivery system, and

a second means for attaching the device to the delivery system at a more proximal location on the delivery system than the first means for attaching,

wherein the relative movement of the first means for attaching and the second means for attaching changes the configuration of the device from the expanded profile configuration to the reduced profile, wherein at least one of first and second means for attaching is a threaded connection.

42. An apparatus to occlude an aperture within a body, the apparatus including a medical device having a first configuration as a reduced profile and a second configuration as an expanded profile, a delivery system adapted to deliver to a desired delivery location, the apparatus comprising:

a proximal side and a distal side,

a first attachment on one of the proximal and distal sides of the device for securing the device to the delivery system, and

a second attachment on the other of the proximal and distal sides of the device for securing the device to the delivery system,

wherein the relative movement of the second attachment and the first attachment changes the configuration of the device from the reduced profile to the expanded profile, and

at least one of the first attachment and second attachment includes interlocking members, one attached to each of the delivery apparatus and the device, to secure the device to the delivery apparatus and a sheath surrounding the interlocking members that

is adapted to release the interlocking members when moved in the axial direction relative to the device.

43. The apparatus recited in claim 42, wherein the interlocking members are on the second attachment and further includes a recess in the device and a cooperating projection on the delivery system that fits the recess.

44. The apparatus recited in claim 43, wherein the apparatus further comprises a tube from which the pins extend and the sheath moves axially with respect to the tube.

45. The apparatus recited in claim 43, wherein the tube includes axially projecting fingers.

46. The apparatus recited in claim 44, wherein the tube includes 4 fingers.

47. The apparatus recited in claim 43, wherein the recess is an annular groove.

48. The apparatus recited in claim 45, wherein the fingers are biased in the radially outward direction.

49. The apparatus recited in claim 48, wherein the fingers include a first bend to extend the device in the radially outward direction and a second bend such that the distal end of the finger is in the axial direction.

50. The apparatus recited in claim 42, wherein the first attachment is a threaded fastener.

51. A method for retrieving a medical device from a desired retrieval location in a body, the method including:

locating the retrieval system at the desired retrieval location,

attaching one of the proximal or distal sides of the device to the retrieval system,

attaching the other of the proximal or distal sides of the device to the retrieval

system, and

causing relative movement of the proximal and distal sides of the device thereby changing the configuration of the device from the expanded profile configuration to the reduced profile configuration,

wherein at least one of the means for attaching does not include twisting.

52. A medical apparatus including a medical device for occluding an aperture in a body and a delivery system, the medical device having a first configuration as a reduced profile and a second configuration as an expanded profile, the medical device being adapted to be delivered through the delivery system into a desired delivery location, the medical device comprising:

a proximal side and a distal side,

a first attachment for securing device to the delivery system that includes a threaded connection between the device and the delivery system, and

a second attachment for securing device to the delivery system that includes a threaded connection between the device and the delivery system,

wherein the relative movement of the second attachment and the first attachment changes the configuration of the device from the reduced profile configuration to the expanded profile configuration and both the first attachment and second attachments are releasable by unscrewing the threaded connection.

53. The medical apparatus recited in claim 52, wherein the first attachment is disposed at a central axis of the device and is released from the delivery device by unscrewing.

54. The medical apparatus recited in claim 52, wherein the second attachment is a threaded connection with threads disposed on the surface of the device and is releasable from the delivery device by unscrewing.

55. The medical apparatus recited in claim 52, wherein the threads associated with the first attachment are unscrewed with a different rotational direction than the threads associated with the second attachment.

56. The medical apparatus recited in claim 52, wherein the threads associated with the first attachment are unscrewed with the same rotational direction as the threads associated with the second attachment.

57. The medical device recited in claim 1, wherein one of the first and second attachments uses a suture.

58. The apparatus recited in claim 18, wherein one of the first and second attachments includes a suture.

59. The apparatus recited in claim 42, wherein the first attachment is a threaded connection disposed at a central axis of the device and is released from the delivery device by twisting.

60. The medical device recited in claim 42, wherein the first attachment is a threaded connection disposed on a surface of the device and is released from the delivery device by twisting.

61. The medical device recited in claim 42, wherein the recess in the device is an annular groove.

62. The medical device recited in claim 42, wherein the device includes an outer surface and an annular groove located on the outer surface.

63. The medical device recited in claim 42, wherein the device includes an outer surface and the recess is located on the outer surface.

64. The medical device recited in claim 42, wherein the annular groove is adapted to receive a plurality of radially inwardly facing projections.








Fig. 1






Fig. 3A




Fig. 2E




Fig. 3B




Fig. 4A












Fig. 4B







0
b
11

66




Fig. 11




Fig 21






FIG. 13








Fig. 16










FIG. 17



*Fig. 20**Fig. 21*






Fig. 25A




Fig. 25B




Fig. 26A




Fig. 26B




Fig. 27A




Fig. 27B




Fig. 28




Fig. 29




Fig. 30




Fig. 31




Fig. 32A

Fig. 32B








Fig. 33








FIG. 38A




FIG. 38B




Fig. 38C




Fig. 38D

